

PA BOOSTER AMPLIFIER (19" RACK/DESK-TOP MOUNTING)



BAP-240



BAP-120



| ТҮРЕ | BOOSTER AMPLIFIER | |
|---------------------------|---|-------------------|
| MODEL | BAP-240 | BAP-120 |
| POWER SUPPLY | AC 115/230V 50/60Hz, DC 24V | |
| POWER OUTPUT | 240W RMS | 120W RMS |
| TOTAL HARMONIC DISTORTION | ≦1% @ 1 KHZ | |
| SENSITIVITY | $1\mathrm{V},100\mathrm{mV}$ @ $10\mathrm{K}\Omega$ | |
| FREQUENCY RESPONSE | 50 Hz-20K Hz +/- 3dB | |
| LOW OUT FILTER | 315Hz - 3dB | |
| OUTPUT | $100\mathrm{V}$, $70\mathrm{V}$, 8Ω | |
| SIGNAL TO NOISE RATIO | 86dB | |
| AC POWER CONSUMPTION | 640W @ RATED POWER | 320W@ RATED POWER |
| DC POWER CONSUMPTION | 15 A @ RATED POWER | 8A @ RATED POWER |
| DIMENSION | 88mm×425mm×305mm (H W D) | |
| WEIGHT | 10.6KGS | 8.2KGS |
| MOUNTING | FREE STANDING OR 19" RACK | |