





SPECIFICATIONS:

MODEL NO.		CS-5H	CS-5HT	CS-6H30	СЅ-6НТ30	CS-6H60	СЅ-6НТ60
Speakers	Bass	5" P.P. Coating Rubber Surround		6-1/2" P.P. Coating Rubber Surround			
	Treble	High Efficiency Tweeter		High Efficiency Tweeter			
Power Rating (100V)		30W	100V, 30W-15W-7.5W-3.75W	30W	100V, 30W-15W-7.5W-3.75W	60W	100V, 60W-30W-15W-7.5W
Impedance		8Ω	333 Ω -667 Ω -1333 Ω -2667 Ω	8Ω	333 Ω -667 Ω -1333 Ω -2667 Ω	8Ω	167Ω -333 Ω -667 Ω -1333 Ω
Sound Pressure Level (at 1W/1M)		96 dB		97 dB		98 dB	
Maximum Acoustic Pressure		111 dB		112 dB		116 dB	
Frequency Response (-10dB)		120 Hz~13K Hz		100 Hz~13K Hz			
Frequency Response (-20dB)		90 Hz~20K Hz		80 Hz~20K Hz			
IP Rating		IEC 60529 IP 66		IEC 60529 IP 66			
Dimensions		$315(W) \times 215(L) \times 355.5(H) \text{ mm}$		415(W)×334(L)×391(H) mm			
Material		ABS Plastic		ABS Plastic			
Colour		Grey (RAL 7035)		Grey (RAL 7035)			
Weight		4.35 Kg	4.65 Kg	6.1 Kg	6.45 Kg	6.5 Kg	7.05 Kg
Mounting Bracket		Steel U Type Bracket		Steel U Type Bracket			

^{*}Building-in Ceramic Terminal Block & Thermo-Fuse is Available Upon Request.



