

**PLASTIC POWER HORN SPEAKER  
(WATER RESISTANT IP66 RATING)**



**SPECIFICATIONS**

Model No.	PHP-60	PHP-100	PHP-60T	PHP-100T
Rated Power	60W	100W	60W	100W
Power Rating(100V)	N.A		60W-30W-15W-7.5W	100W-50W-25W-12.5W
Power Rating(70V)	N.A		30W-15W-7.5W-3.75W	50W-25W-12.5W-6.25W
Impedance	16Ω (AC at 1KHz)	16Ω (AC at 1KHz)	167Ω-333Ω-667Ω-1333Ω	100Ω-200Ω-400Ω-800Ω
S.P.L.( at 1W/1M )	103dB	106dB	103dB	106dB
MAX. S.P.L.( at Rated W/1M )	120dB	126dB	120dB	126dB
Frequency Response(-20dB)	340 ~ 10KHz	300 ~ 9KHz	340 ~ 10KHz	300 ~ 9KHz
Dispersion 1KHz / 4KHz	360° / 40°	360° / 40°	360° / 40°	360° / 40°
IP Rating	<b>IEC60529 IP66</b>			
Power Selection	2-core cable		5-core cable	
Dimension	146(Dia) x 161(L)mm		146(Dia) x 227(L)mm	
Material	Housing : High impact ABS with UV inhibitors			
Colour	Light Grey (RAL 7035)			
Weight	2.1Kg	2.1Kg	2.7Kg	2.7Kg
Mounting	U Type Aluminum Alloy Bracket			

