

WALL MOUNT AUTOFORMER VOLUME CONTROL

- 10 STEPS PLUS OFF POSITION ATTENUATION @3dB EACH
- FINAL 2 STEPS@6dB EACH TOTAL ATTENUATION AT 33dB
- WORKING WITH 4 OR 8 OHMS SPEAKER
- FREQUENCY RESPONSE FOR ALL UNIT IS 35Hz~20kHz AT RATED POWER



PLASTIC FRONT PANEL AND KNOB.

VC-4091P MONO 6W RMS 100V
 VC-4092P MONO 12W RMS 100V
 VC-4093P MONO 24W RMS 100V
 VC-4094P MONO 35W RMS 100V
 VC-4095P MONO 50W RMS 100V
 VC-4100P MONO 100W RMS 100V
 VC-4091PR MONO+RELAY 6W RMS 100V
 VC-4092PR MONO+RELAY 12W RMS 100V
 VC-4093PR MONO+RELAY 24W RMS 100V
 VC-4094PR MONO+RELAY 35W RMS 100V
 VC-4095PR MONO+RELAY 50W RMS 100V
 VC-4100PR MONO+RELAY 100W RMS 100V

- These series are designed with the priority line for the purpose of emergency announcement or paging.
- Dimensions : 85(L) × 85(H) × 49(D)mm
(Mounting Depth : 40mm)



MODEL SMF-409 SURFACE MOUNT FRAME

- Suitable For VC-4091/VC-4100
- Plastic Material.
- Dimensions : 84(L) × 84(H) × 52(D)mm



PLASTIC FRONT PANEL AND KNOB.

VC-5093P MONO 6W RMS 100V
 VC-5094P MONO 12W RMS 100V
 VC-5095P MONO 24W RMS 100V
 VC-5096P MONO 35W RMS 100V
 VC-5097P MONO 50W RMS 100V
 VC-5098P MONO 75W RMS 100V

- These series are designed with the priority line for the purpose of emergency announcement or paging.
- Dimensions : 115.7(L) × 71(H) × 49(D)mm
(Mounting Depth : 44mm)